

Preva Operating System 7.2.8

Restoring the Ability to Update Non-Networked Px2 Consoles via USB.

Applies to

Non-Networked P62 and P82 consoles.

When to Use

This new release should be used in non-networked facilities until consoles are shipping with 7.2.8. Networked locations will be updated via remote updates.

- Installing a new console or replacing a console under warranty.
 - Precor does not provide warranty reimbursements for proactive updates of previously installed consoles. In some instances software updates will change the user interface, creating a mismatch with other consoles in the facility.

What's New/Changed

- Certificate updates allowing the ability to USB update Px2 consoles.
- General software and video optimizations have been made to increase stability and performance.

How to Acquire

This release will not be provided via the normal software download process. In order to install this release, providing future USB flash drive update capabilities, you must order the CS SW REFLASH KIT for the product type you are updating.

P62: CX50078-101

P82: CX50077-101

These kits will contain a preformatted storage microSD card, along with instructions on how to recover the ability to update via USB. Any stand-alone release will not work until those steps are performed.



Caution: If you use a rescue SD or standard USB with software prior to 7.2.8, you will return the console to the previous state. This kit will need to be used in order to recover USB flashing (unless you have a new rescue SD card with 7.2.8 or later). The 7.2.8 build will be the new baseline build moving forward. The ability to USB flash to a previous version will be blocked.



Note: The microSD card included in this kit is **NOT** a rescue SD. Flashing with it will not require settings and registration to be redone, so do not use this SD as a rescue SD. Due to the caution above, it is recommended to discard all rescue SD cards with software prior to 7.2.8 and replace them with their respective part numbers:

P62: 304335-109

P82: 58198-113

As part of the kit there are work instructions providing a download link for an autorun script. The work instructions explain how to use the autorun script, however you can acquire this software ahead of receiving the re-flash kit in order to be fully equipped once the kit arrives. The file is very small (4KB) and should take only a few seconds to download.

<https://tinyurl.com/yc9mn27w>.